

時規皮帶輪各式形狀



A	AF	AWF																																						
B	BF	BWF																																						
D	DF	<table border="1"> <thead> <tr> <th colspan="2">PL Material</th> <th>S45C</th> <th>AL6061</th> </tr> </thead> <tbody> <tr> <td>t</td> <td>T</td> <td></td> <td></td> </tr> <tr> <td>1.2</td> <td></td> <td>1.8</td> <td>1.7</td> </tr> <tr> <td>1.6</td> <td></td> <td>2.4</td> <td>2.2</td> </tr> <tr> <td>2.0</td> <td></td> <td colspan="2">2.8</td> </tr> <tr> <td>2.3</td> <td></td> <td colspan="2">3.1</td> </tr> <tr> <td>3.0</td> <td></td> <td colspan="2">螺絲鎖固</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Belt Pitch</th> <th>BW=Belt Width</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>W=BW+(≧1)</td> </tr> <tr> <td>3-5</td> <td>W=BW+(≧1.5)</td> </tr> <tr> <td>8</td> <td>W=BW+(≧2)</td> </tr> <tr> <td>≧14</td> <td>W=BW+(≧4)</td> </tr> </tbody> </table> <p>備註:1.W,T,t(參左圖) Unit:mm 2.以上均為建議值</p>	PL Material		S45C	AL6061	t	T			1.2		1.8	1.7	1.6		2.4	2.2	2.0		2.8		2.3		3.1		3.0		螺絲鎖固		Belt Pitch	BW=Belt Width	2	W=BW+(≧1)	3-5	W=BW+(≧1.5)	8	W=BW+(≧2)	≧14	W=BW+(≧4)
PL Material		S45C	AL6061																																					
t	T																																							
1.2		1.8	1.7																																					
1.6		2.4	2.2																																					
2.0		2.8																																						
2.3		3.1																																						
3.0		螺絲鎖固																																						
Belt Pitch	BW=Belt Width																																							
2	W=BW+(≧1)																																							
3-5	W=BW+(≧1.5)																																							
8	W=BW+(≧2)																																							
≧14	W=BW+(≧4)																																							